

PIT gb LLTE

G1000028



PITgatebox (按钮单元)，带控制元件和急停按钮的预组装外壳，40 mm 宽，带急停按钮（2个常闭触点）、2个发光按钮（各1个常开触点）以及1个发光按钮（1个常闭触点）的接线盒，连接12针M12连接器，IP65，包含绿色、蓝色、红色、黄色盖 以及透明盖

技术细节

般数据

Approval:	CE, UL/cUL, UKCA, EAC (Eurasian)
自检:	nein
灯:	LED
灯泡颜色:	weiß

技术数据

电气数据

供电电压 (V):	24, 24
电源电压类型U1:	DC
功率消耗DC:	12
最小接触电流:	1

紧急停止

数量, E-STOP N/C:	2
急停释放类型:	Drehentriegelung
急停按钮切换能力达标:	EN 60947-5-1
急停按钮触点材料:	Ag

按钮

数量, 按钮:	2
常开按钮的数量:	2
按钮切换能力达标:	EN 60947-5-1

按钮触点材料:	Ag
环境数据	
以摄氏度一表示的环境温度:	-20, 60
气候适宜性标准:	EN 60068-2-78
湿度额定值:	93 % r.h.40 °C
振动测试所依据的标准:	EN 60947-5-2
冲击应力测试所依据的标准1规定的加速度:	30g
应遵守的间隙与爬电距离标准:	EN 60947-1
过电压等级:	三
间隙与爬电距离污染程度规范:	3
UL外壳类型:	1 类
机械数据	
安装位置:	任意
连接类型:	M12, 12pol. male
外壳材料:	Zn
高度尺寸:	293
宽度尺寸:	40
深度尺寸:	40
净重:	800
总重:	1200
环境	
WEEE klassifikation (08/2018):	5 devices (feed size < 50cm)
商业数据	
Harmonized System Code:	85365019
UNSPSC 25:	39122205
EAN代码:	4046548097795
eClass 版本:	ECLASS-13
eTIM 版本:	ETIM-9.0
eTIM 参考组:	EG000017

ETIM 引用功能:	EC000225
卷宗:	0

必选的操作配件

	570356	PSEN cable M12-12sf 50m
	570354	PSEN cable M12-12sf 20m
	570355	PSEN cable M12-12sf 30m
	570352	PSEN cable M12-12sf 5m
	570353	PSEN cable M12-12sf 10m
	570350	PSEN cable M12-12sf 2m
	570351	PSEN cable M12-12sf 3m

可选的配件



G1000010

PIT gb blind cover



G1000012

PIT gb fixing spanner



G1000013

PIT gb color cover wh s1



G1000014

PIT gb color cover wh s2



G1000015

PIT gb color cover wh s3



G1000016

PIT gb color cover wh s4



G1000017

PIT gb color cover bl s5



G1000018

PIT gb color cover bl s6



G1000019

PIT gb color cover bl s4

G1000009

PIT gb color covers

